

WS1 SERIES SNAP ACTION SWITCH

ANTI-VANDAL SWITCHES
DETECTOR SWITCHES
DIP SWITCHES
KEYLOCK SWITCHES
NAVIGATION SWITCHES
PUSHBUTTON SWITCHES
ROCKER SWITCHES
ROTARY SWITCHES
SLIDE SWITCHES
SNAP ACTION SWITCHES
TACTILE SWITCHES
TOGGLE SWITCHES
CAP OPTIONS



APPLICATIONS / MARKETS



HVAC



Electrical Housewares




Floor Care Appliances



White Goods



Vending Machines



Medical Equipment

RoHS

SPECIFICATIONS

Contact Rating: 01 = 0.1A @ 48VDC
0.1A @ 125VAC, 250VAC
3 = 3A @ 12VDC
3A @ 125VAC, 250VAC

Contact Resistance: 150mΩ Max.

Insulation Resistance: 100MΩ Max.

Dielectric Strength: 500VAC for 1 minute

Electrical Life: 100,000 Cycles MIN.

Mechanical Life: 500,000 Cycles MIN.

Operating Temperature: -40°C to 85°C

Moisture Protection: IP67

Operating Force: 130 gf MAX.

FEATURES & BENEFITS

- Current rating options
- Multiple termination options
- IP67 rated

PART NUMBER CONFIGURATOR

Series	Operating Temperature	Current Rating	Actuator	Operating Force	Termination	Circuit
WS1	085 - 85°C	01 - 0.1A @ 48VDC
0.1A @ 125VAC, 250VAC
3 - 3A @ 125VDC
3A @ 125VAC, 250VAC	00 - Pin Plunger	F130 - 130 gf	S - Solder Lug
W - Wire Leads (162mm Length)	A - SPDT

Specifications subject to change without notice 3.14.2022



E-SWITCH®

www.e-switch.com




800.867.2717

1

BODY DIMENSIONS - SOLDER LUG

O.P. (MM)	F.P. (MM)
6.40~6.95	7.35 MAX

O.P. = OPERATING POINT
F.P. = FREE-POSITION




WS1 SERIES SNAP ACTION SWITCH


BODY DIMENSIONS - WIRE LEADS

O.P. (MM)	F.P. (MM)
6.40~6.95	7.35 MAX

O.P. = OPERATING POINT
F.P. = FREE-POSITION



SWITCH	WIRE	LENGTH
SW1-1 (COM)	WIRE, 24AWG UL1007 STRANDED, BLACK	162.0 [6.38 in]
SW1-2 (NO)	WIRE, 24AWG UL1007 STRANDED, YELLOW	162.0 [6.38 in]
SW1-3 (NC)	WIRE, 24AWG UL1007 STRANDED, BLUE	162.0 [6.38 in]



E-SWITCH®

www.e-switch.com

800.867.2717

3